

NANOMYTE® NAB-65E

Active Material Characteristics

Product IDs:	NAB-65E (single-sided) NAB-65E-DS (double-sided)
Product Description:	Sodium Ferric Pyrophosphate electrode sheets
Formula:	Na ₄ Fe ₃ (PO ₄) ₂ (P ₂ O ₇)
Average Particle Size (D₅₀):	6.5 μm
Specific Surface Area:	7.4 m ² /g

Electrode Tape Characteristics

Current Collector:	Aluminum (16 μm thick)
Sheet Dimensions:	5 in x 10 in (127 mm x 254 mm); coated edge-to-edge
Calendared:	Yes
Electrode Coating:	Single or Double-sided sheets (as specified)
Coating Thickness:	100 μm ± 5% (excluding current collector)
Standard Expected Areal Capacity:	1.0 mAh/cm ² ± 5% (per side)
Active Material Loading:	10.0 mg/cm ² ± 5% (per side)

Standard Tape Composition:

Wt. %	Material	Description
90%	Sodium Ferric Pyrophosphate	(active material)
5%	Poly(vinylidene fluoride) ["PVDF"]	(binder)
5%	Carbon Black ["Super P"]	(conductive carbon)

*Specifications can be modified upon request to accommodate different active material loadings, coating thickness, & capacity.

Electrochemical Characteristics

Nominal Voltage vs. Na/Na⁺:	3.0 V
Minimum First Discharge Capacity:	90 mAh/g (1.5 – 3.8 V @ 0.1C)
Typical First Discharge Capacity:	95 mAh/g (1.5 – 3.8 V @ 0.1C)

Available Quantities

Electrode sheets are available in packs of 2, 5, 10, 25, 50, & 100 sheets. Bulk quantities are available upon request.

Precautions for Safe Storage & Handling

Handling: Appropriate personal protective equipment should be used at all times. Avoid contact with eyes and skin. Handle in a dry and well-ventilated area. Avoid actions that abrade, sand, or grind the coated surface, which can release respirable dust.

Storage: Store sheets flat and in a cool, dry place, away from heat and moisture.

Note: In its manufactured and shipped form, this article does not pose a physical hazard or health risk to humans or the environment. However, processing that generates dust or exposure to extreme temperatures may release hazardous particles.

Refer to SDS for complete safety information of this material.

NOTE: NEI Corporation believes that the information in this spec sheet is an accurate description of the typical use of the product. However, NEI disclaims any liability for incidental or consequential damages, which may result from the use of their products that are beyond its control. Employers should use this information only as a supplement to other information gathered by them and should make independent judgment of suitability of this information to ensure proper use and protect the health and safety of employees. Therefore, it is the user's responsibility to thoroughly test the product in their particular application to determine its performance, efficacy, and safety. Nothing contained herein is to be considered as permission or a recommendation to infringe any patent or any other intellectual right.